



PLATFORM

PXA270 624MHz Processor

1GB Flash ROM

256MB RAM

OPERATING SYSTEM

Windows CE 5 Standard Edition / Windows Mobile 6 Classic Professional (optional)

WIRELESS COMMUNICATION

Integrated Bluetooth Classic II, V2.0 + EDR

EXTERNAL CONNECTORS

One Tether Connection with full RS232 and USB On-The Go (USB1.1) Functionality

One Low-Insertion Force (LIF) Docking Connector

DC Power Jack

USER INTERFACE

3.7 inch Color and Touch Screen

Full VGA 480 X 640 Resolution

Transflective, Portrait Mode TFT

Sunlight Readable (for outdoor use)

Adjustable LED

Backlight

165cd/m2 Output

Passive Stylus or Finger Operation

Signature Capture

Full Alphanumeric Keyboard

Backlight, High Durability Hard-capped Keys

EXPANSION SLOTS

One SD/MMC Memory Card Slot

End-cap USB Interface Supports GPS Expansion Module

100-pin Expansion Interface: Supports PCMCIA (Type 2), GPRS/EDGE and other 3-Party Expansion Modules Developed Using Psion Hardware Developer's Kit

One Type II CF Card Slot

POWER SUPPLY

Optional 3.7V, 2700mAh Standard Capacity Battery

Advanced Smart Battery with Gauge

Built-in Charger

Rechargeable, Replaceable Backup Battery Pack

WORKING ENVIRONMENT

Withstands Multiple Drops from 1.8m or 26 Drops (on 12 Edges, 6 Corners, 8 Faces) from 1.5m to Concrete Ground while Power is on

Waterproof/Dustproof: IP65, IEC 60529

Operation Temperature: -20°C ~ +50°C

5% - 95% RH Non-condensing

Storage Temperature: -40°C ~ +60°C

ESD: ±8k Vdc Air Discharge, ±4k Vdc Contacts

PHYSICAL

Dimension: 223 X 100 X 42mm

Weight: 0.46kg without Battery
